

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (Previously Presented) A monitoring device configured to monitor a remote status of mobile assets, comprising:

a position location unit configured to determine a location of a remote device;

a simplex satellite transmitter configured to transmit the location to one or more satellites in low earth orbit;

a power source; and

a controller including a power management unit configured to control a power state of the position location unit and the simplex satellite transmitter, and to periodically enable and disable power from the power source to the position location unit and the simplex satellite transmitter.

2. (Previously Presented) The monitoring device of claim 1, wherein the position location unit comprises a GPS receiver subsystem.

3. (Previously Presented) The monitoring device of claim 1, wherein the power source comprises a battery.

4. (Previously Presented) The monitoring device of claim 1, wherein each of the one or more satellites operate as a bent-pipe relay device.

5. (Previously Presented) The monitoring device of claim 1, wherein the controller further comprises:

an external interface having at least one of a plurality of alarm inputs, a configuration interface configured to receive modifications to configuration parameters, and an external data unit configured to receive external data,

wherein the power management unit is further configured to control a power state of the external interface and to periodically enable and disable power from the power source to the external interface.

6. (Previously Presented) The monitoring device of claim 5, wherein the power management unit is further configured to disable power and then enable power on an interval schedule.

7. (Previously Presented) The monitoring device of claim 6, wherein the controller is further configured to control the position location unit to determine the location and the simplex satellite transmitter to transmit the location on the interval schedule.

8. (Previously Presented) The monitoring device of claim 7, wherein the interval schedule is a repeated fixed interval.

9. (Previously Presented) The monitoring device of claim 7, wherein the interval schedule is a set of fixed intervals sequentially executed and repeated as a set.

10. (Previously Presented) The monitoring device of claim 7, wherein the interval schedule is adjusted with a randomization term to pseudo-randomly vary the interval schedule.

11. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect at least one of the plurality of alarm inputs, and upon detection of an alarm input, to control the simplex satellite transmitter to transmit alarm data.

12. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect at least one of the plurality of alarm inputs, and upon detection of an alarm input, to enable power to the simplex satellite transmitter and the position location unit, and to control the position location unit to determine the location and the simplex satellite transmitter to transmit the location and alarm data.

13. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect at least one of the plurality of alarm inputs, and upon detection of an alarm input, to enable power to the external interface.

14. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect modifications to the configuration parameters, and upon detection of modifications to the configuration parameters, to modify operation in accordance with the configuration parameters.

15. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect external data from the external data unit, and upon detection of external data, to control the simplex satellite transmitter to transmit the external data.

16. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to queue transmissions to the simplex satellite transmitter and to control the simplex satellite transmitter to transmit the queued transmissions as a block to reduce on-air traffic.

17. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to control the simplex satellite transmitter to periodically transmit a health status of the remote device.

18. (Previously Presented) The monitoring device of claim 7, further comprising a motion detection unit.

19. (Previously Presented) The monitoring device of claim 18, wherein the controller is configured to control the position location unit to determine the location and the simplex satellite transmitter to transmit the location upon detection by the motion detection unit of motion.

20. (Previously Presented) The monitoring device of claim 18, wherein the controller is configured to control the simplex satellite transmitter to transmit a motion detection message upon a detection by the motion detection unit of a stop of motion followed by a start of motion.

21. (Previously Presented) The monitoring device of claim 18, wherein the controller is configured to control the simplex satellite transmitter to transmit a motion cease message upon a detection by the motion detection unit of a start of motion followed by a stop of motion.

22. (Previously Presented) A method for monitoring a remote status of mobile assets, comprising:

- a) determining a location of a remote device;
- b) transmitting the location using a simplex satellite transmitter to one or more satellites in low earth orbit;
- c) receiving at least one of a plurality of alarm inputs, configuration parameters, and external data from an external data unit; and
- d) managing power to perform steps a) - c) periodically on an interval schedule to reduce power consumption.

23. (Previously Presented) The method of claim 22, wherein the managing step comprises:

repeating steps a) - c) at fixed intervals.

24. (Previously Presented) The method of claim 22, wherein the managing step comprises:

repeating steps a) - c) at a set of unique fixed intervals sequentially executed and repeated as a set.

25. (Previously Presented) The method of claim 22, wherein the managing step comprises:

repeating steps a) - c) adjusted with a randomization term to pseudo-randomly vary a repeating time.

26. (Previously Presented) The method of claim 22, further comprising:

e) transmitting the alarm data using a simplex satellite transmitter to one or more satellites in low earth orbit upon receiving at least one of the plurality of alarm inputs.

27. (Previously Presented) The method of claim 22, further comprising:

e) detecting a change in motion state of the remote device and, upon detection of motion state change, performing step b) to transmit the location.

28. (Previously Presented) A computer program product configured to store plural computer program instructions which, when executed by a computer, cause the computer to perform the steps recited in any one of claims 22-27.

29. (Previously Presented) A securing device for a device enclosure comprising:

a mounting tab having a surface and a V-cut molded into the surface forming a deflection, and

wherein the mounting tab is molded into the device enclosure such that the removal of the mounting tab is enabled through deflection of the mounting tab.

30. (Previously Presented) A low-profile weather-proof enclosure device comprising:

a base wall;

a lid secured to the base wall; and
a gasket positioned between the base wall and the lid,
wherein the lid includes an overlapping wall which overlaps the base wall and extends below the gasket, and wherein the overlapping wall provides rigidity and a water barrier to the gasket.

31. (Previously Presented) The low-profile weather-proof enclosure device of claim 30, wherein the low-profile weather-proof enclosure device contains a monitoring device that comprises:

a position location unit configured to determine a location of a remote device;
a radio transmitter configured to transmit the location; and
a power source configured to provide power to the monitoring device.

32. (Previously Presented) The low-profile weather-proof enclosure device of claim 30, further comprising break-away mounting tabs secured to the base wall.

33. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect at least one of the plurality of alarm inputs, and upon detection of an alarm input, to enable or disable an alternate interval schedule for transmit of information.

34. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect a change of state of motion, and upon detection of motion state change, to enable or disable an alternate interval schedule for transmit of information.

35. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect a trigger location, and upon detection of trigger location, to enable or disable an alternate interval schedule for transmit of information.

36. (Previously Presented) The monitoring device of claim 7, wherein the controller is configured to detect at least one of the plurality of alarm inputs while in low power inventory mode, and upon detection of an alarm input in low power inventory mode, to transition to run mode to begin service as set by previous configuration.

37. (New) A monitoring device configured to monitor a remote status of a mobile device, comprising:

a position location unit configured to determine a location of the mobile device;

a transmitter configured to transmit the location to one or more satellites;

a power source;

an integral motion determination means for initiating an alternate behavior of the monitoring device; and

a controller including a power management unit configured to control a power state of the position location unit and the transmitter, and periodically or on alarm determination to enable and disable power from the power source to the position location unit and the simplex satellite transmitter.